



(1) EC-Type Examination Certificate

- (2) Equipment or protective system intended for use in potentially explosive atmospheres Directive 94/9/EC
- (3) Examination certificate number: SEV 08 ATEX 0164

(4) Equipment:

Handlight Type UK4AA - E*** resp. UK 4AA ELED CPO - ***

(5) Manufacturer:

Underwater Kinetics

(6) Address:

13400 Danielson Street, US-Poway, CA 92064, USA

- (7) The equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- (8) Electrosuisse SEV, notified body No. 1258 in accordance with article 9 of the Council Directive of the European Communities of 23 March 1994 (94/9/EC), certifies that this equipment has been found to comply with the essential health and safety requirements relating to the design and construction of equipment or protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The results of the examination are recorded in confidential report no 08-IK-0392.01 incl. extension 1 to 4.

(9) Compliance with the essential health and safety requirements has been assured by compliance with:

EN 1127-1:2007

EN 60079-0:2006

EN 60079-7:2007

EN 60079-11:2007

EN 61241-0:2006

EN 61241-11:2006

- (10) If the sign «X» is placed after the certificate number, it indicates that the equipment or protective system is subjected to special conditions for safe use specified in the schedule to this certificate.
- (11) This examination certificate relates only to design and construction of the specified equipment in accordance with the directive 94/9/EC. Further requirements of this directive apply to the manufacturing process and the placing on the market of the equipment.
- (12) The marking of the equipment shall include the following:

see appendix page 4: (19) Marking

Electrosuisse

Certification Body ATEX

Fehraltorf, 2011-05-04

Martin Plüss Product Certification Replaces certificate dated 2010-11-09 Extension 4; modification

page 1 of 4





(13)

Appendix

(14)

EC-Type Examination Certificate SEV 08 ATEX 0164

(15) Description of the equipment

The handlight Type UK4AA – E*** resp. UK 4AA ELED CPO - *** is a universal lamp suitable for use in potentially explosive atmospheres zones 1 and 21. The light source in the lamp head consists of either an LED unit or an incandescent light bulb unit. Depending on the particular model, the lamp is switched on and off with a pushbutton on the side or back or by screwing and unscrewing the lamp head. The used batteries are primary cells. Depending on the particular model, the lamp housing has a special clip for attaching to Gallet firemen's helmets.

The Handlight Type UK4AA - E*** may be alternatively provided with a right angle adapter.

Ratings

For type UK4AA – E***		
Batteries (Alkaline)	Voltage (U)	ELED element
4 x DURACELL PROCEL; LR6 / AA / MN1500	6.0V (4x1.5V)	14849
4 x DURACELL PLUS; LR6 / AA / MN1500	6.0V (4x1.5V)	14849
4 x Energizer Industial; LR6 / AA / EN91 / AM3	6.0V (4x1.5V)	14849

or

Batteries (Alkaline)	Voltage (U)	Light bulb element
4 x DURACELL; LR6 / AA / MN1500	6.0V (4x1.5V)	14801
4 x DURACELL PLUS; LR6 / AA / MN1500	6.0V (4x1.5V)	14801
4 x Energizer Industial; LR6 / AA / EN91 / AM3	6.0V (4x1.5V)	14801

or

For type UK 4AA ELED CPO - ***		
Batteries (Alkaline)	Voltage (U)	ELED module
4 x DURACELL PROCEL; LR6 / AA / MN1500	6.0V (4x1.5V)	14875-A
4 x DURACELL PLUS; LR6 / AA / MN1500	6.0V (4x1.5V)	14875-A
4 x Energizer Industial; LR6 / AA / EN91 / AM3	6.0V (4x1.5V)	14875-A





Appendix to EC-Type Examination Certificate SEV 08 ATEX 0164

Notes

- According to Directive 94/9/EC (ATEX 95), Appendix I, the handlight Type UK4AA E***
 resp. UK 4AA ELED CPO *** is a device of equipment group II, category 2G, which
 according to Directive 99/92/EC (ATEX 137) can be used in zones 1 and 2 and gas
 groups IIA, IIB and IIC, which are potentially explosive due to the presence of flammable
 materials in the temperature classes T1 to T4.
- 2. According to Directive 94/9/EC (ATEX 95), Appendix I, the handlight Type UK4AA E*** resp. UK 4AA ELED CPO *** is also a device of equipment group II, category 2D, which according to Directive 99/92/EC (ATEX 137) can be used in zones 21 and 22 subject to combustible dusts.
- 3. The permissible ambient temperature range is -20°C to +40°C.
- 4. The Handlight Type UK4AA E*** resp. UK 4AA ELED CPO *** must not be opened in potentially explosive atmospheres or in the presence of combustible dusts.
- 5. Only the batteries and the lamp elements specified in the ratings must be used.
- Only to be used are batteries of the same electrochemical system, same cell construction and nominal capacity and same manufacturer.
- 7. For the Handlight Type UK4AA E*** provided with a right angle adapter the information (instructions) issue no. 400845, 400846, 400844, 400843 and 400848 needs to be used as basic information as well.





Appendix to EC-Type Examination Certificate SEV 08 ATEX 0164

(16) Test Report

08-IK-0392.01 incl. extension 1 to 4

- (17) Special conditions for safe use
- (18) <u>Fundamental essential health and safety requirements</u>
 Fulfilled by the standards applied
- (19) Marking

Ex e ib IIC T4
II 2D Ex ibD 21 T98°C



ElectrosuisseCertification Body ATEX

Martin Plüss Product Certification Fehraltorf, 2011-05-04

Replaces certificate dated 2010-11-09 Extension 4; modification

page 4 of 4